Material Safety Data Sheet



May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY: WT-103 Flame Retardant Clear - Matte Coating

Section I - Product Identification

| Manufacturer's Name FireTect, Inc. | Emergency Telephone Number: (661) 295-Fire (3473) | |
|---|---|--|
| Address: 28298 Constellation Rd. Valencia, CA 91355 | Telephone Number for Information: (661) 295-3473 | |
| | Date Prepared: 01-10-95 Reviewed: 01-2014 | |

Section II - Hazardous Ingredients

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | OSHA PEL None | ACGIH TLV None | Other Limits Recommended None | %(optional) | |
|---|------------------|---|-------------------------------------|-------------|--|
| Firetect WT-103 Flame retardant coating | | 21.8% Inorganic Phosphates | | | |
| Non-Hazardous coating water based latex | | 18.4 % modified polyvivylidene chloride copolymer | | | |
| VOC: 47 Grams per liter | | 3.4% sodium salt aromatic sulfonate | | | |
| NON-HAZARDOUS, NON FLAMMABLE | | 41.9% liquid vehicle | | | |
| NFPA: Hazardous 0, Flammability 0 Reactivity 0 | | | | | |
| DOT Classification: None | | | | | |

Section III - Physical Data/Chemical Characteristics

| Boiling Point | 212° F | Specific Gravity (H ₂ O = 1) 1.08 | | |
|--|----------------|--|-----------------|--|
| Vapor Pressure (mm Hg.) | None | Melting Point | None | |
| Vapor Density (AIR = 1) | Equal to water | Evaporation Rate (Butyl Acetate = 1) | Less than water | |
| Solubility in Water: Complete - dilutable in water | | | | |
| Appearance and Odor: milky white liquid (clears as it dries) | | | | |

Section IV - Fire and Explosion Hazard Data

| Flash Point (Method Used): None | Flammable Limit: None | LEL: None | VEL: None | |
|--|--------------------------|--------------|--------------|--|
| Extinguishing Media: For dry solids use water foam CO ₂ or dry chemical fire fighting apparatus | | | | |
| Special Fire Fighting Procedures: Closed container exposed to heat may rupture due to pressure build up | | | | |
| Unusual Fire and Explosion Hazards: | | | | |

Section V - Reactivity Data

| Stability | Stable | X | Conditions | to Avoid | I: None |
|--|----------------|------|------------|----------|---------------------------|
| Incompatibility (Materials to Avoid): None | | | | | |
| Hazardous Decomposition or Byproducts: | | | | | |
| Hazardous | Polymerization | Will | Not Occur | X | Conditions to Avoid: None |

Section VI - Health Hazard Data

| Route(s) of Entry: Inhalation Yes | Skin Yes Ingestion Unlikely | |
|-----------------------------------|-----------------------------|--|
|-----------------------------------|-----------------------------|--|

Health Hazards (*Acute and Chronic*): Inhalation: Overexposure may cause irritation. If not breathing give artificial respiration seek medical attention. Skin Contact: cleanse affected areas with mild soap and water. If irritation develops, seek medical attention. Ingestion: if drowsy or unconscious, place victim on left side with head down. Do not give anything by mouth; seek medical attention.

Carcinogenicity: none according to Ames Test NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure: Local Irritation

Medical Conditions Generally aggravated by Exposure: If irritation or redness develops from exposure move victim away from source and into fresh air. Seek medical attention.

Emergency and First Aid Procedures: In case of eye contact, flush with running water for at least 15 minutes. If irritation persists, seek advice of a physician.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts may be absorbed into appropriate absorbent.

Waste Disposal Method: Dispose of product in accordance with applicable local, county, state and federal regulation..

Precautions to Be taken in Handling and Storing: Keep containers in cool, dry area. Use and store with adequate ventilation.

Other Precautions: Storage should not exceed 80° or fall below 40°. Do not allow to freeze. Once opened, contents should be used completely.

Section VIII - Control Measure

| Respiratory Protection (Specify Type): Not mandatory. | | | | |
|---|----------------------|---|--|--|
| Ventilation Local Exhaust: S | | Special | | |
| | Mechanical (General) | Other | | |
| Protective Gloves: use of gloves that are impermeable to product is advised | | Eye Protection: approved eye protection to protect against eye contact or irritation is recommended | | |
| Other Protective Clothing or Equipment | | | | |
| Work/Hygienic Pavailable for flushi | | nilk soap & water; it is recommended that clean water be | | |